



**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF BOE HF AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE HF AND MUST BE RETURNED TO BOE HF UPON ITS REQUEST

S864-6023

PRODUCT GROUP  
TFT MODULE

Rev. A


ISSUE DATE  
2011.7.19

PAGE  
1 OF30

**TITLE : B3 HT215F01-100**  
**Product Specification For Qisda**  
**Rev. A**


HEFEI BOE OPTOELECTRONICS TECHNOLOGY CO., LTD.



|  |   |     |                 |
|--|---|-----|-----------------|
|  <b>京东方<br/>BOE</b> | PRODUCT GROUP   | REV | ISSUE DATE      |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19       |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda_ Rev.A |     | PAGE<br>2 OF 30 |


REVISION HISTORY

| REV. | ECN No. | DESCRIPTION OF CHANGES             | DATE       | PREPARED     |
|------|---------|------------------------------------|------------|--------------|
| 0    |         | Initial Release                    | 2011.07.04 | jiangweidong |
| A    |         | Frame Period 1149 lines→1251 lines | 2011.07.06 | jiangweidong |
|      |         |                                    |            |              |
|      |         |                                    |            |              |
|      |         |                                    |            |              |
|      |         |                                    |            |              |
|      |         |                                    |            |              |
|      |         |                                    |            |              |
|      |         |                                    |            |              |
|      |         |                                    |            |              |

|  |   |     |                 |
|--|---|-----|-----------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE      |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19       |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>3 OF 30 |

## Contents


| No.  | Item   | Page |
|------|--|------|
| 1.0  | General Description                                  | 4    |
| 2.0  | Absolute Maximum Ratings                             | 6    |
| 3.0  | Electrical Specifications                            | 7    |
| 4.0  | Optical Specifications                               | 8    |
| 5.0  | Interface Connection                                 | 10   |
| 6.0  | Signal Timing Specifications                         | 13   |
| 7.0  | Signal Timing Waveforms of Interface Signal          | 15   |
| 8.0  | Input Signals, Display Colors & Gray Scale of Colors | 17   |
| 9.0  | Power Sequence                                       | 18   |
| 10.0 | Mechanical Characteristics                           | 19   |
| 11.0 | Reliability Test                                     | 20   |
| 12.0 | Handling& Cautions                                   | 21   |
| 13.0 | Product Serial Number                                | 22   |
| 14.0 | Packing  | 23   |
| 15.0 | Appendix   | 25   |

|  |   |     |                 |
|--|---|-----|-----------------|
|  <b>京东方</b><br><b>BOE</b> | PRODUCT GROUP   | REV | ISSUE DATE      |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19       |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>4 OF 30 |

## 1.0 GENERAL DESCRIPTION


### 1.1 Introduction

HT215F01-100 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 21.5 inch diagonally measured active area with FHD resolutions (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.7M colors. The TFT-LCD panel used for this module is adapted for a low reflection and higher color type.



### 1.2 Features

- LVDS Interface with 2 pixel / clock
- High-speed response
- 6-bit (Hi-FRC) color depth, display 16. 7M colors
- Incorporated edge type back-light (One Light Bar)
- High luminance and contrast ratio, low reflection and wide viewing angle
- DE (Data Enable) only
- RoHS /TCO 5.0 Compliant

|  |   |     |                 |
|--|---|-----|-----------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE      |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19       |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>5 OF 30 |

### 1.3 Application


- Desktop Type of PC & Workstation Use
- Slim-Size Display for Stand-alone Monitor
- Display Terminals for Control System
- Monitors for Process Controller

### 1.4 General Specification

The followings are general specifications at the model HT215F01-100.

<Table 1. General Specifications>

| Parameter           | Specification                      | Unit   | Remarks |
|---------------------|------------------------------------|--------|---------|
| Active area         | 476.64(H) × 268.11 (V)             | mm     |         |
| Number of pixels    | 1920(H) × 1080(V)                  | pixels |         |
| Pixel pitch         | 0.24825(H) × 0.24825(V)            | mm     |         |
| Pixel arrangement   | RGB Vertical stripe                |        |         |
| Display colors      | 16.7M                              | colors |         |
| Display mode        | Normally White                     |        |         |
| Dimensional outline | 495.6(H) × 292.2(V) × 10.2(D) typ. | mm     |         |
| Weight              | 1450 (typ.)                        | g      |         |
| Surface Treatment   | Haze 25%, 3H                       |        |         |
| Back-light          | Lower side 1-LED Light bar Type    |        |         |

|  |   |     |                 |
|--|---|-----|-----------------|
|  京东方<br>BOE | PRODUCT GROUP   | REV | ISSUE DATE      |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19       |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>6 OF 30 |


## 2.0 ABSOLUTE MAXIMUM RATINGS


The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings> [VSS=GND=0V]

| Parameter             | Symbol   | Min.    | Max.         | Unit | Remarks    |
|-----------------------|----------|---------|--------------|------|------------|
| Power Supply Voltage  | $V_{DD}$ | -0.5    | 5.5          | V    | Ta = 25 °C |
| Logic Supply Voltage  | $V_{IN}$ | VSS-0.3 | $V_{DD}+0.3$ | V    |            |
| Operating Temperature | $T_{OP}$ | 0       | +50          | °C   | 1)         |
| Storage Temperature   | $T_{ST}$ | -20     | +60          | °C   | 1)         |

Note : 1) Temperature and relative humidity range are shown in the figure below.  
Wet bulb temperature should be 39 °C max. and no condensation of water.



|  |   |     |                 |
|--|---|-----|-----------------|
|  京东方<br>BOE | PRODUCT GROUP   | REV | ISSUE DATE      |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19       |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>7 OF 30 |

### 3.0 ELECTRICAL SPECIFICATIONS

#### 3.1 Electrical Specifications

< Table 3. Electrical specifications >

[Ta =25 ± 2 ℃]


| Parameter                                       |                    | Min.   | Typ.  | Max. | Unit | Remarks  |
|---|--------------------|--------|-------|------|------|--|
| Power Supply Voltage                            | V <sub>DD</sub>    | 4.5    | 5.0   | 5.5  | V    | Note1  |
| Power Supply Current                            | I <sub>DD</sub>    | -      | 700   | 1400 | mA   |  |
| In-Rush Current                                 | I <sub>RUSH</sub>  | -      | -     | 3    | A    | Note 2   |
| Permissible Input Ripple Voltage                | V <sub>RF</sub>    | -      | -     | 100  | mV   | V <sub>DD</sub> = 5.0V                             |
| High Level Differential Input Threshold Voltage | V <sub>IH</sub>    | -      | -     | +100 | mV   |  |
| Low Level Differential Input Threshold Voltage  | V <sub>IL</sub>    | -100   | -     | -    | mV   |  |
| Differential input voltage                      | V <sub>ID</sub>    | 200    | -     | 600  | mV   |  |
| Differential input common mode voltage          | V <sub>cm</sub>    | 1.0    | 1.2   | 1.5  |      | V <sub>IH</sub> =100mV,<br>V <sub>IL</sub> =-100mV |
| LED Channel Voltage                             | V <sub>L</sub>     | -      | 54.4  | 59.5 | V    |  |
| LED Channel Current                             | I <sub>L</sub>     | -      | 60    | -    | mA   |  |
| LED Lifetime                                    |                    | 30,000 | -     | -    | Hrs  | I <sub>L</sub> =60 mA                              |
| Power Consumption                               | P <sub>D</sub>     | -      | 3.5   | -    | W    |  |
|   | P <sub>BL</sub>    | -      | 13.06 | -    | W    | I <sub>L</sub> =60 mA, Note 5                      |
|   | P <sub>total</sub> | -      | 16.56 | -    | W    |  |

Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.

The current draw and power consumption specified is for VDD=5.0V, Frame rate=75Hz. Test Pattern of power supply current

a) Typ : Color Bar pattern

b) Max : Skip Sub Pixel Pattern




2. Duration of rush current is about 2 ms and rising time of VDD is 520 μs ± 20 %

3. The lamp frequency should be selected as different as possible from the horizontal

synchronous frequency and its harmonics to avoid interference, which may cause line flow on the display

4. The voltage above this value should be applied to the lamps for more than 1 second to start-up. Otherwise the lamps may not be turned on.

5. Calculated value for reference (V<sub>L</sub> × I<sub>L</sub>) × 4(channel) excluding driver loss. (LED Light bar: 17S4P)

|  |  |     |                        |
|--|--|-----|------------------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>   | REV | ISSUE DATE             |
|  | PRODUCT SPEC-TFT MODULE  | A   | 2011.7.19              |
| S864-6023  | <b>SPEC. TITLE</b><br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | <b>PAGE</b><br>8 OF 30 |

## 4.0 OPTICAL SPECIFICATION

### 4.1 Overview


The test of Optical specifications shall be measured in a dark room (ambient luminance  $\leq 1$  lux and temperature =  $25 \pm 2^\circ\text{C}$ ) with the equipment of Luminance meter system (Goniometer system and TOPCONE BM-5) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of  $\Theta$  and  $\Phi$  equal to  $0^\circ$ . We refer to  $\Theta_{\Phi=0}$  ( $=\Theta_3$ ) as the 3 o'clock direction (the "right"),  $\Theta_{\Phi=90}$  ( $=\Theta_{12}$ ) as the 12 o'clock direction ("upward"),  $\Theta_{\Phi=180}$  ( $=\Theta_9$ ) as the 9 o'clock direction ("left") and  $\Theta_{\Phi=270}$  ( $=\Theta_6$ ) as the 6 o'clock direction ("bottom"). While scanning  $\Theta$  and/or  $\Phi$ , the center of the measuring spot on the Display surface shall stay fixed. The measurement shall be executed after 30 minutes warm-up period. VDD shall be 5.0V +/-10% at  $25^\circ\text{C}$ . Optimum viewing angle direction is 6 'clock.

### 4.2 Optical Specifications

[VDD = 5.0V, Frame rate = 60Hz, Clock = 78MHz,  $I_{BL} = 7.5\text{mA}$ ,  $T_a = 25 \pm 2^\circ\text{C}$ ]

| Parameter                  |            | Symbol        | Condition  | Min.  | Typ.  | Max.  | Unit              | Remark |
|----------------------------|------------|---------------|--|-------|-------|-------|-------------------|--------|
| Viewing Angle range        | Horizontal | $\Theta_3$    | CR > 10  | 70    | 85    | -     | Deg.              | Note 1 |
|                            |            | $\Theta_9$    |  | 70    | 85    | -     | Deg.              |        |
|                            | Vertical   | $\Theta_{12}$ |  | 70    | 80    | -     | Deg.              |        |
|                            |            | $\Theta_6$    |  | 70    | 80    | -     | Deg.              |        |
| Viewing Angle range        | Horizontal | $\Theta_3$    | CR > 5   | 85    | -     | -     | Deg.              |        |
|                            |            | $\Theta_9$    |  | 85    | -     | -     | Deg.              |        |
|                            | Vertical   | $\Theta_{12}$ |  | 85    | -     | -     | Deg.              |        |
|                            |            | $\Theta_6$    |  | 85    | -     | -     | Deg.              |        |
| Luminance Contrast ratio   |            | CR            | $\Theta = 0^\circ$<br>(Center)<br>Normal<br>Viewing<br>Angle | 700   | 1000  |       |                   | Note 2 |
| Luminance of White         |            | $Y_w$         |  | 200   | 250   |       | cd/m <sup>2</sup> | Note 3 |
| White luminance uniformity |            | $\Delta Y$    |  | 75    | 80    |       | %                 | Note 4 |
| Reproduction of color      | White      | $W_x$         |  | 0.283 | 0.313 | 0.343 |                   | Note 5 |
|                            |            | $W_y$         |  | 0.299 | 0.329 | 0.359 |                   |        |
|                            | Red        | $R_x$         |  | 0.609 | 0.639 | 0.669 |                   |        |
|                            |            | $R_y$         |  | 0.312 | 0.342 | 0.372 |                   |        |
|                            | Green      | $G_x$         |  | 0.293 | 0.323 | 0.353 |                   |        |
|                            |            | $G_y$         |  | 0.600 | 0.630 | 0.660 |                   |        |
|                            | Blue       | $B_x$         |  | 0.123 | 0.153 | 0.183 |                   |        |
|                            |            | $B_y$         |  | 0.021 | 0.051 | 0.081 |                   |        |
| Response Time              | Rising     | $T_r$         |  |       | 1.5   | 2.5   | ms                | Note 6 |
|                            | Falling    | $T_f$         |  |       | 3.5   | 5.5   | ms                |        |
| Cross Talk                 |            | CT            |  | -     | -     | 2.0   | %                 | Note 7 |




|  |   |     |                 |
|--|---|-----|-----------------|
|  <b>京东方<br/>BOE</b> | PRODUCT GROUP   | REV | ISSUE DATE      |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19       |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>9 OF 30 |

**Note :**

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface.
2. Contrast measurements shall be made at viewing angle of  $\theta = 0^\circ$  and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state. (See FIGURE 1 shown in Appendix) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.
4. The White luminance uniformity on LCD surface is then expressed as :  
 $\Delta Y = ( \text{Minimum Luminance of 9points} / \text{Maximum Luminance of 9points} ) * 100$   
 (See FIGURE 2 shown in Appendix).
5. The color chromaticity coordinates specified in Table 4. shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
6. The electro-optical response time measurements shall be made as FIGURE 3 shown in Appendix by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is Td, and 90% to 10% is Tr.
7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance ( $Y_A$ ) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance ( $Y_B$ ) of that same area when any adjacent area is driven dark. (See FIGURE 4 shown in Appendix).

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>10 OF 30 |

## 5.0 INTERFACE CONNECTION.

### 5.1 Electrical Interface Connection

- CN1      Module Side Connector : UJU IS100-L300-C23 or Equivalent  
                  User Side Connector : JAE FI-X30H or Equivalent

| Pin No | Symbol | Function                                     | Remark |
|--------|--------|--|--------|
| 1      | RX00-  | Negative Transmission data of Pixel 0 (ODD)  |        |
| 2      | RX00+  | Positive Transmission data of Pixel 0 (ODD)  |        |
| 3      | RX01-  | Negative Transmission data of Pixel 1 (ODD)  |        |
| 4      | RX01+  | Positive Transmission data of Pixel 1 (ODD)  |        |
| 5      | RX02-  | Negative Transmission data of Pixel 2 (ODD)  |        |
| 6      | RX02+  | Positive Transmission data of Pixel 2 (ODD)  |        |
| 7      | GND    | Power Ground                                 |        |
| 8      | RXOC-  | Negative Transmission Clock (ODD)            |        |
| 9      | RXOC+  | Positive Transmission Clock (ODD)            |        |
| 10     | RX03-  | Negative Transmission data of Pixel 3 (ODD)  |        |
| 11     | RX03+  | Positive Transmission data of Pixel 3 (ODD)  |        |
| 12     | RXE0-  | Negative Transmission data of Pixel 0 (EVEN) |        |
| 13     | RXE0+  | Positive Transmission data of Pixel 0 (EVEN) |        |
| 14     | GND    | Power Ground                                 |        |
| 15     | RXE1-  | Negative Transmission data of Pixel 1 (EVEN) |        |
| 16     | RXE1+  | Positive Transmission data of Pixel 1 (EVEN) |        |
| 17     | GND    | Power Ground                                 |        |
| 18     | RXE2-  | Negative Transmission data of Pixel 2 (EVEN) |        |
| 19     | RXE2+  | Positive Transmission data of Pixel 2 (EVEN) |        |
| 20     | RXEC-  | Negative Transmission Clock (EVEN)           |        |
| 21     | RXEC+  | Positive Transmission Clock (EVEN)           |        |
| 22     | RXE3-  | Negative Transmission data of Pixel 3 (EVEN) |        |
| 23     | RXE3+  | Positive Transmission data of Pixel 3 (EVEN) |        |
| 24     | GND    | Power Ground                                 | Note1  |
| 25     | NC     | Not connection, this pin should be open      |        |
| 26     | NC     | Not connection, this pin should be open      |        |
| 27     | NC     | Not connection                               |        |
| 28     | VDD1   | Power Supply: +5V                            |        |
| 29     | VDD2   |  |        |
| 30     | VDD3   |  |        |

Note 1 : This pin should be connected with GND



# PRODUCT GROUP

REV

ISSUE DATE

PRODUCT SPEC-TFT MODULE

A

2011.7.19

S864-6023

SPEC. TITLE

B3 HT215F01-100 Product Specification For Qisda \_Rev.A

PAGE

11 OF 30

## 5.2 LVDS Interface (Tx; THC63LVDF83A or Equivalent)

### 5.2.1 ODD LVDS Interface

|                                     | Input Signal | Transmitter |          | Interface            |                      | HT215F01-100 (CN11) | Remark |
|-------------------------------------|--------------|-------------|----------|----------------------|----------------------|---------------------|--------|
|                                     |              | Pin No.     | Pin No.  | System (Tx)          | TFT-LCD (Rx)         | Pin No.             |        |
| O<br>D<br>D<br><br>L<br>V<br>D<br>S | OR0          | 51          | 48<br>47 | OUT0-<br>OUT0+       | RX00-<br>RX00+       | 1<br>2              |        |
|                                     | OR1          | 52          |          |                      |                      |                     |        |
|                                     | OR2          | 54          |          |                      |                      |                     |        |
|                                     | OR3          | 55          |          |                      |                      |                     |        |
|                                     | OR4          | 56          |          |                      |                      |                     |        |
|                                     | OR5          | 3           |          |                      |                      |                     |        |
|                                     | OG0          | 4           | 46<br>45 | OUT1-<br>OUT1+       | RX01-<br>RX01+       | 3<br>4              |        |
|                                     | OG1          | 6           |          |                      |                      |                     |        |
|                                     | OG2          | 7           |          |                      |                      |                     |        |
|                                     | OG3          | 11          |          |                      |                      |                     |        |
|                                     | OG4          | 12          |          |                      |                      |                     |        |
|                                     | OG5          | 14          |          |                      |                      |                     |        |
|                                     | OB0          | 15          | 42<br>41 | OUT2-<br>OUT2+       | RX02-<br>RX02+       | 5<br>6              |        |
|                                     | OB1          | 19          |          |                      |                      |                     |        |
|                                     | OB2          | 20          |          |                      |                      |                     |        |
|                                     | OB3          | 22          |          |                      |                      |                     |        |
|                                     | OB4          | 23          |          |                      |                      |                     |        |
|                                     | OB5          | 24          |          |                      |                      |                     |        |
|                                     | Hsync        | 27          | 40<br>39 | CLK OUT-<br>CLK OUT+ | RX0 CLK-<br>RX0 CLK+ | 8<br>9              |        |
|                                     | Vsync        | 28          |          |                      |                      |                     |        |
|                                     | DE           | 30          | 38<br>37 | OUT3-<br>OUT3+       | RX03-<br>RX03+       | 10<br>11            |        |
|                                     | MCLK         | 31          |          |                      |                      |                     |        |
|                                     | OR6          | 50          |          |                      |                      |                     |        |
|                                     | OR7          | 2           |          |                      |                      |                     |        |
|                                     | OG6          | 8           |          |                      |                      |                     |        |
|                                     | OG7          | 10          |          |                      |                      |                     |        |
|                                     | OB6          | 16          |          |                      |                      |                     |        |
|                                     | OB7          | 18          |          |                      |                      |                     |        |
|                                     | RSVD         | 25          |          |                      |                      |                     |        |



# PRODUCT GROUP

REV

ISSUE DATE

PRODUCT SPEC-TFT MODULE

A

2011.7.19

S864-6023

SPEC. TITLE


B3 HT215F01-100 Product Specification For Qisda \_Rev.A

PAGE


12 OF 30

## 5.2.2 EVEN LVDS Interface

|  | Input Signal | Transmitter |          | Interface      |                | HT215F01-100 (C N11) | Remark |
|--|--------------|-------------|----------|----------------|----------------|----------------------|--------|
|  |              | Pin No.     | Pin No.  | System (Tx)    | TFT-LCD (Rx)   | Pin No.              |        |
| E<br>V<br>E<br>N<br><br>L<br>V<br>D<br>S | ER0          | 51          | 48<br>47 | OUT0-<br>OUT0+ | RXE0-<br>RXE0+ | 12<br>13             |        |
|  | ER1          | 52          |          |                |                |                      |        |
|  | ER2          | 54          |          |                |                |                      |        |
|  | ER3          | 55          |          |                |                |                      |        |
|  | ER4          | 56          |          |                |                |                      |        |
|  | ER5          | 3           |          |                |                |                      |        |
|  | EG0          | 4           | 46<br>45 | OUT1-<br>OUT1+ | RXE1-<br>RXE1+ | 15<br>16             |        |
|  | EG1          | 6           |          |                |                |                      |        |
|  | EG2          | 7           |          |                |                |                      |        |
|  | EG3          | 11          |          |                |                |                      |        |
|  | EG4          | 12          |          |                |                |                      |        |
|  | EG5          | 14          |          |                |                |                      |        |
|  | EB0          | 15          | 42<br>41 | OUT2-<br>OUT2+ | RXE2-<br>RXE2+ | 18<br>19             |        |
|  | EB1          | 19          |          |                |                |                      |        |
|  | EB2          | 20          |          |                |                |                      |        |
|  | EB3          | 22          |          |                |                |                      |        |
|  | EB4          | 23          |          |                |                |                      |        |
|  | EB5          | 24          |          |                |                |                      |        |
|  | Hsync        | 27          | 38<br>37 | OUT3-<br>OUT3+ | RXE3-<br>RXE3+ | 22<br>23             |        |
|  | Vsync        | 28          |          |                |                |                      |        |
|  | DE           | 30          |          |                |                |                      |        |
|  | MCLK         | 31          |          |                |                |                      |        |
|  |              |             |          |                |                |                      |        |
|  | ER6          | 50          |          |                |                |                      |        |
|  | ER7          | 2           |          |                |                |                      |        |
|  | EG6          | 8           |          |                |                |                      |        |
|  | EG7          | 10          |          |                |                |                      |        |
|  | EB6          | 16          |          |                |                |                      |        |
|  | EB7          | 18          |          |                |                |                      |        |
|  | RSVD         | 25          |          |                |                |                      |        |

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>13 OF 30 |


5.3 Data Input Format



5.4 Back-light Interface Connection

● CN 2                      LED LightBar Connector :CI1406M1HRL-NH or equivalent

| Pin | Function                   |
|-----|----------------------------|
| 1   | Channel 1 Current Feedback |
| 2   | Channel 2 Current Feedback |
| 3   | LED Power Supply           |
| 4   | LED Power Supply           |
| 5   | Channel3 Current Feedback  |
| 6   | Channel4 Current Feedback  |

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>14 OF 30 |

## 6.0 SIGNAL TIMING SPECIFICATION

6.1 The HT215F01-100 is operated by the DE only.


| Item                      |           | Symbols | Min  | Typ    | Max   | Unit   |
|---------------------------|-----------|---------|------|--------|-------|--------|
| Clock                     | Frequency | 1/Tc    | 57.5 | 74.32  | 94    | MHz    |
|                           | High Time | Tch     | -    | 4/7 Tc | -     |        |
|                           | Low Time  | Tcl     | -    | 3/7 Tc | -     |        |
| Frame Period              |           | Tv      | 1091 | 1125   | 1251  | lines  |
|                           |           |         | 50   | 60     | 75    | Hz     |
|                           |           |         | 20   | 16.67  | 13.33 | ms     |
| Vertical Display Period   |           | Tvd     | -    | 1080   | -     | lines  |
| One line Scanning Period  |           | Th      | 1060 | 1100   | 1251  | clocks |
| Horizontal Display Period |           | Thd     | -    | 960    | -     | clocks |

## 6.2 LVDS Rx Interface Timing Parameter


The specification of the LVDS Rx interface timing parameter is shown in Table 4.

<Table 4. LVDS Rx Interface Timing Specification>

| Item         | Symbol | Min             | Typ         | Max             | Unit | Remark |
|--------------|--------|-----------------|-------------|-----------------|------|--------|
| CLKIN Period | tRCIP  | 10.76           | 13.46       | 16.15           | nsec |        |
| Input Data 0 | tRIP1  | -0.4            | 0.0         | +0.4            | nsec |        |
| Input Data 1 | tRIP0  | tRCIP/7-0.4     | tRCIP/7     | tRCIP/7+0.4     | nsec |        |
| Input Data 2 | tRIP6  | 2 × tRCIP/7-0.4 | 2 × tRCIP/7 | 2 × tRCIP/7+0.4 | nsec |        |
| Input Data 3 | tRIP5  | 3 × tRCIP/7-0.4 | 3 × tRCIP/7 | 3 × tRCIP/7+0.4 | nsec |        |
| Input Data 4 | tRIP4  | 4 × tRCIP/7-0.4 | 4 × tRCIP/7 | 4 × tRCIP/7+0.4 | nsec |        |
| Input Data 5 | tRIP3  | 5 × tRCIP/7-0.4 | 5 × tRCIP/7 | 5 × tRCIP/7+0.4 | nsec |        |
| Input Data 6 | tRIP2  | 6 × tRCIP/7-0.4 | 6 × tRCIP/7 | 6 × tRCIP/7+0.4 | nsec |        |




$$* V_{diff} = (RXz+) - (RXz-), \dots, (RxCCLK+) - (RxCCLK-)$$

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>16 OF 30 |


7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL

7.1 Sync Timing Waveforms



- 1) Need over 3 H-sync during V-Sync Low
- 2) Fix H-Sync width from V-Sync falling edge to first rising edge

7.2 Vertical Timing Waveforms







# PRODUCT GROUP

REV

ISSUE DATE

PRODUCT SPEC-TFT MODULE

A

2011.7.19

S864-6023



SPEC. TITLE


B3 HT215F01-100 Product Specification For Qisda \_Rev.A

PAGE

17 OF 30


## 7.3 Horizontal Timing Waveforms



|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>18 OF 30 |


## 8.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

| Color & Gray Scale  |          | RED DATA |    |    |    |    |    |    |    | GREEN DATA |    |    |    |    |    |    |    | BLUE DATA |    |    |    |    |    |    |    |
|---------------------|----------|----------|----|----|----|----|----|----|----|------------|----|----|----|----|----|----|----|-----------|----|----|----|----|----|----|----|
|                     |          | R7       | R6 | R5 | R4 | R3 | R2 | R1 | R0 | G7         | G6 | G5 | G4 | G3 | G2 | G1 | G0 | B7        | B6 | B5 | B4 | B3 | B2 | B1 | B0 |
| Basic Colors        | Black    | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | Blue     | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1         | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
|                     | Green    | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1          | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | Cyan     | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1          | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1         | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
|                     | Red      | 1        | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | Magenta  | 1        | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1         | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
|                     | Yellow   | 1        | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1          | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | White    | 1        | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1          | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1         | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
| Gray Scale of RED   | Black    | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | △        | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | Darker   | 0        | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | △        | ↑        |    |    |    |    |    |    |    | ↑          |    |    |    |    |    |    |    | ↑         |    |    |    |    |    |    |    |
|                     | ▽        | ↓        |    |    |    |    |    |    |    | ↓          |    |    |    |    |    |    |    | ↓         |    |    |    |    |    |    |    |
|                     | Brighter | 1        | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | ▽        | 1        | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | Red      | 1        | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
| Gray Scale of GREEN | Black    | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | △        | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | Darker   | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | △        | ↑        |    |    |    |    |    |    |    | ↑          |    |    |    |    |    |    |    | ↑         |    |    |    |    |    |    |    |
|                     | ▽        | ↓        |    |    |    |    |    |    |    | ↓          |    |    |    |    |    |    |    | ↓         |    |    |    |    |    |    |    |
|                     | Brighter | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1          | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | ▽        | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1          | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | Green    | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1          | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
| Gray Scale of BLUE  | Black    | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | △        | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 1  |
|                     | Darker   | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 1  | 0  |
|                     | △        | ↑        |    |    |    |    |    |    |    | ↑          |    |    |    |    |    |    |    | ↑         |    |    |    |    |    |    |    |
|                     | ▽        | ↓        |    |    |    |    |    |    |    | ↓          |    |    |    |    |    |    |    | ↓         |    |    |    |    |    |    |    |
|                     | Brighter | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1         | 1  | 1  | 1  | 1  | 1  | 0  | 1  |
|                     | ▽        | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1         | 1  | 1  | 1  | 1  | 1  | 1  | 0  |
|                     | Blue     | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1         | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
| Gray Scale of WHITE | Black    | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                     | △        | 0        | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0          | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0         | 0  | 0  | 0  | 0  | 0  | 0  | 1  |
|                     | Darker   | 0        | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0          | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0         | 0  | 0  | 0  | 0  | 1  | 0  | 0  |
|                     | △        | ↑        |    |    |    |    |    |    |    | ↑          |    |    |    |    |    |    |    | ↑         |    |    |    |    |    |    |    |
|                     | ▽        | ↓        |    |    |    |    |    |    |    | ↓          |    |    |    |    |    |    |    | ↓         |    |    |    |    |    |    |    |
|                     | Brighter | 1        | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 1          | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 1         | 1  | 1  | 1  | 1  | 1  | 0  | 1  |
|                     | ▽        | 1        | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 1          | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 1         | 1  | 1  | 1  | 1  | 1  | 1  | 0  |
|                     | White    | 1        | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1          | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1         | 1  | 1  | 1  | 1  | 1  | 1  | 1  |

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>19 OF 30 |

## 9.0 POWER SEQUENCE


To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



- $0.5 \text{ ms} \leq T1 \leq 10 \text{ ms}$
- $0 \leq T2 \leq 50 \text{ ms}$
- $0 \leq T3 \leq 50 \text{ ms}$
- $1 \text{ sec} \leq T4$
- $200 \text{ ms} \leq T5$
- $200 \text{ ms} \leq T6$

### Notes:

1. When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
2. Do not keep the interface signal high impedance when power is on.
3. Back Light must be turn on after power for logic and interface signal are valid.

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>20 OF 30 |

## 10.0 MECHANICAL CHARACTERISTICS

### 10.1 Dimensional Requirements

FIGURE 6 (located in Appendix) shows mechanical outlines for the model HT215F01-100. Other parameters are shown in Table 5.

<Table 5. Dimensional Parameters>

| Parameter           | Specification                                | Unit   |
|---------------------|--|--------|
| Dimensional outline | 495.6 × 292.2 × 10.2                         | mm     |
| Weight              | 1450 (typ.)                                  | gram   |
| Active area         | 476.64(H) × 268.11(V)                        | mm     |
| Pixel pitch         | 0.24825(H) x 0.24825(V)                      | mm     |
| Number of pixels    | 1920(H) × 1080(V) (1 pixel = R + G + B dots) | pixels |
| Back-light          | Lower side 1-LED Light bar Type              |        |

### 10.2 Mounting


See FIGURE 5. (shown in Appendix)

### 10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an anti-glare coating to minimize reflection and a coating to reduce scratching.

### 10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.


|  |   |     |                  |
|--|---|-----|------------------|
|  京东方<br>BOE | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>21 OF 30 |

## 11.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.


<Table 6. Reliability Test Parameters >

| No | Test Items                                       | Conditions  |                                |
|----|--|---|--------------------------------|
| 1  | High temperature storage test                    | Ta = 60 °C , 240 hrs                                      |                                |
| 2  | Low temperature storage test                     | Ta = -20 °C , 240 hrs                                     |                                |
| 3  | High temperature & high humidity operation test  | Ta = 50 °C , 80%RH, 240hrs                                |                                |
| 4  | High temperature operation test                  | Ta = 50 °C , 240hrs                                       |                                |
| 5  | Low temperature operation test                   | Ta = 0 °C , 240hrs  |                                |
| 6  | Thermal shock                                    | Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle                   |                                |
| 7  | Vibration test<br>(non-operating)                | Frequency   | 10 ~ 300 Hz, Sweep rate 30 min |
|    |  | Gravity / AMP   | 1.5 G                          |
|    |  | Period  | X, Y, Z 30 min                 |
| 8  | Shock test<br>(non-operating)                    | Gravity   | 50G                            |
|    |  | Pulse width   | 11msec, sine wave              |
|    |  | Direction   | ± X, ± Y, ± Z Once for each    |
| 9  | Electro-static discharge test<br>(non-operating) | Air : 150 pF, 330Ω, 15 KV<br>Contact : 150 pF, 330Ω, 8 KV |                                |
| 10 | Altitude test                                    | Operating: 0 to 16400ft , 0 to 40°                        |                                |
|    |  | Non Operating: 0 to 40000ft, -20 to 40°                   |                                |

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>22 OF 30 |

## 12.0 HANDLING & CAUTIONS

- (1) Cautions when taking out the module
  - Pick the pouch only, when taking out module from a shipping package.
- (2) Cautions for handling the module
  - As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
  - As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
  - As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
  - Do not pull the interface connector in or out while the LCD module is operating.
  - Put the module display side down on a flat horizontal plane.
  - Handle connectors and cables with care.
- (3) Cautions for the operation
  - When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
  - Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.
- (4) Cautions for the atmosphere
  - Dew drop atmosphere should be avoided.
  - Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.
- (5) Cautions for the module characteristics
  - Do not apply fixed pattern data signal to the LCD module at product aging.
  - Applying fixed pattern for a long time may cause image sticking.
- (6) Other cautions
  - Do not disassemble and/or re-assemble LCD module.
  - Do not re-adjust variable resistor or switch etc.
  - When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方</b><br><b>BOE</b> | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>23 OF 30 |

13.0 PRODUCT SERIAL NUMBER



|     |   |   |     |   |         |             |
|-----|---|---|-----|---|---------|-------------|
| 1   | 2 | 3 | 4   | 5 | 6       | 7           |
| X X | X | X | X X | X | X X X X | X X X X X X |

1. Control Number  
2. Rank / Grade  
3. Line Classification  
4. Year (2001 : 01, 2002 : 02, ...)


5. Month (1,2,3, ... , 9, X, Y, Z)  
6. Internal Use  
7. Serial Number

|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>24 OF 30 |


## 14.0 Packing

### 14.1 Packing Order


Put EPE Cushion into the box




As shown in the figure, place the modules bundled by packing bag In the box




After sealing the box, attach Packing Label on the attach position sign area of the box.




Place EPE cover on top of the box






|  |   |     |                  |
|--|---|-----|------------------|
|  京东方<br>BOE | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>25 OF 30 |


## 14.2 Pallet Packing Order




Load Pallet in correct position



Pile up the unit Box filled with Modules on the Pallet carefully not to make a space.




Adjust Outer box to piling Boxes and cover the Outer box using box cover. Bend Pallet Assy which is putting the Box Cover tight in two direction (horizontal and vertical) and two times using Polyester bend.



Wrap the Pallet Assy loaded 1story, 2stories from downside through side and to edge of upside. (12Boxes/Pallet)




|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方<br/>BOE</b> | <b>PRODUCT GROUP</b>  | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>26 OF 30 |

### 14.3 Packing Specification and Note

| Item                 | Specification  |                                    |             | Remark                  |
|----------------------|----------------|------------------------------------|-------------|-------------------------|
|                      | Q'ty           | Dimension                          | Weight (kg) |                         |
| Panel                | 1              | 495.6(H) × 292.2(V) × 10.2(D) typ. | 1.48        | -                       |
| Cushion              | 1              | -                                  | 0.70        | -                       |
| Box                  | 1              | 558(L)mm x 348(W)mm x 400(H)mm     | 0.70        | without Panel & cushion |
| Packing Box          | 10pcs/Box      | 558(L)mm x 348(W)mm x 400(H)mm     | 16.20       | with panel & cushion    |
| Pallet               | 1              | 1200(L)mm x 1140(W)mm x 120(H)mm   | 15.90       | -                       |
| Pallet after Packing | 12boxes/pallet | 1140(L)mm x 1076(W)mm x 820(H)mm   | 214         | -                       |


### 14.3 Box label

- Label Size : 108 mm (L) × 56 mm (W)
- Contents
  - Model : HT215F01-100
  - Q'ty : Module Q'ty in one box
  - Serial No. : Box Serial No. See next page for detail description.
  - Date : Packing Date
  - FG Code : FG Code of Product


**京东方  
BOE**
**HEFEI BOE OPTOELECTRONICS TECHNOLOGY**

MODEL: HT215F01-100  
 SERIAL NO: 0000000000000000


Q'TY: 10  
 DATE: 201X.X.XX




\*QAA0330000268\*

00 0 00 0 0 000000  
 Type Grade Year Month ITEM-CODE Serial\_no

5940  
 FG CODE


 RoHS Mark

|  |   |     |                  |
|--|---|-----|------------------|
|  京东方<br>BOE | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>27 OF 30 |

15.0 APPENDIX

Figure 1. Measurement Set Up





Figure 2. White Luminance and Uniformity Measurement Locations (9 points)




|  |   |     |                  |
|--|---|-----|------------------|
|  京东方<br>BOE | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>28 OF 30 |

Figure 3. Response Time Testing






Figure 4. Cross Modulation Test Description



Cross-Talk (%) =  $\left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$

Where:  $Y_A$  = Initial luminance of measured area (cd/m<sup>2</sup>)  
 $Y_B$  = Subsequent luminance of measured area (cd/m<sup>2</sup>)  
The location measured will be exactly the same in both patterns

**Figure 5. TFT-LCD Module Outline Dimensions (Front view)**




|  |   |     |                  |
|--|---|-----|------------------|
|  <b>京东方</b><br><b>BOE</b> | PRODUCT GROUP   | REV | ISSUE DATE       |
|  | PRODUCT SPEC-TFT MODULE   | A   | 2011.7.19        |
| S864-6023  | SPEC. TITLE<br>B3 HT215F01-100 Product Specification For Qisda _Rev.A |     | PAGE<br>30 OF 30 |

Figure 6. TFT-LCD Module Outline Dimensions (Rear view)

